



CERTIFICATION : EN 361 : 2002 / EN 1497 : 2007 / REGULATION : 2016 / 425

Dorsal plate in polypropilene with  
fall arrest attachment ringFront attachment points  
(loops to connect together)High resistance webbing  
and stitchesPadded leg straps with  
automatic bucklesSteel D ring on  
back attachmentQuick fastening  
chest strapSteel automatic locking  
buckles on legsSteel quick adjustment  
buckle on shoulders

## TECHNICAL SPECIFICATIONS

- Main webbing in polyester wide 45 mm ( $R \geq 22$  kN)
- Secondary chest strap elastic, wide 25 mm
- Black epoxy coated buckles on shoulders and legs
- Padded leg straps for better comfort
- Static resistance  $\geq 15$  kN
- Weight : 1,2 kg

Other model available on request :

- Back extension strap Ref. : NUS65AEX

## USE

Full body harness for all types of works on height. Intended for industry and construction area. Rescue harness for all kind of rescue works.

## DESCRIPTION

Full body harness and rescue harness NUS65A, offers safety and comfort of use through its automatic buckles on legs and quick buckles on shoulders for easy adjustment.

TAILLE / SIZE	80 cm $\leq$ Size S $\leq$ 105 cm 90 cm $\leq$ Size M-L $\leq$ 115 cm 100 cm $\leq$ Size XL $\leq$ 135 cm
65 cm $\leq$ Size S $\leq$ 105 cm 85 cm $\leq$ Size M-L $\leq$ 120 cm 105 cm $\leq$ Size XL $\leq$ 135 cm	
45 cm $\leq$ Size S $\leq$ 65 cm 50 cm $\leq$ Size M-L $\leq$ 75 cm 60 cm $\leq$ Size XL $\leq$ 80 cm	
155 cm $\leq$ Size S $\leq$ 175 cm 165 cm $\leq$ Size M-L $\leq$ 188 cm 170 cm $\leq$ Size XL $\leq$ 200 cm	