

# FULL BODY HARNESS WITH INTEGRATED WORK POSITIONING BELT

REF.  
NUS55C

neofeu.com

**FALL PROTECTION ONLY\***  
\*Un seul métier, l'antichute

CERTIFICATION : EN 361 : 2002 / EN 358 : 2018 / REGULATION : 2016 / 425



TESTED  
140 KG

Large back fall arrest  
D ring in aluminum

Front fall arrest  
webbing loop

Shoulder straps adjustment  
pulling downwards

Drop indicators

Lateral D ring for work  
positioning in coated  
forged aluminum

Quick buckles for  
leg strap adjustment

## TECHNICAL SPECIFICATIONS

- Tested to 140 kg
- Webbing in polyester 44 mm (  $R \geq 25$  kN )
- Shoulder straps adjustment pulling downwards with black zinc plated quick buckles male/female
- Chest strap 44 mm and legs straps adjustment through black zinc plated quick buckles
- Comfort belt in high density foam fitted with 2 large side D rings in aluminum and 4 tool-holders
- Drop indicators showing at 300 daN
- Static resistance  $\geq 15$  kN
- Weight : 1,5 kg

## USE

Full body harness to use in case of fall hazard. Intended to maintenance works in industry and the construction area.

## DESCRIPTION

Fullbody harness bicolor in polyester webbing with 2 fall arrest attachment points : 1 front loop and 1 back large aluminum D ring. A comfort belt is integrated in high density foam for positioning and 2 large side D rings in aluminium for work restraint. Easy to adjust with slide buckles on shoulder straps, pulling downwards and quick buckles on legs. It is fitted with 2 fall indicators.

